

Benelli

ENTRY TO ADVENTURE

Your next journey starts with Benelli's all-new ultra-friendly TRK 251



TRK 251

TRK 251

Benelli

SPECIFICATIONS

Engine

Type
1-cylinder/4-stroke/4-valve,DOHC

Bore & Stroke
ø78.0x55.2 mm.

Displacement
249 c.c.

Rated Output
20.0kW/10500rpm

Compression Ratio
12:1

Gearbox
6-speed

Lubrication
Pressure splash lubrication

Clutch
Wet multi-plate

Fuel System
EFI

Exhaust System
Long-acting Catalyst

Starting
Electric

Cooling System
Liquid-cooled

Ignition
TLI

Chassis

Frame
Arch bar truck

Front Suspension
Telescopic forks, 135 mm.

Rear Suspension
Telescopic coil spring oil damped, 60 mm.

Front Brake
Disc, diameter 280 mm.

Rear Brake
Disc, diameter 240 mm.

Front Wheel
17 x 3.5 inch

Rear Wheel
17 x 4.0 inch

Front Tire
110/70R17

Rear Tire
150/60R17

Wheelbase
1380 mm.

Ground Clearance
170 mm.

Dry Weight
173 Kg.

Fuel Capacity
18 L.

FULLY DIGITAL DISPLAY

Track your journeys with ease and clarity thanks to the TRK 251's digital instrumentation cluster

INCREDIBLE RANGE

The massive 17-liter fuel tank and excellent efficiency equal hundreds of kilometers between refuelings

NEW-GEN 250cc ENGINE

The smooth, torquey, and reliable 250cc four-stroke, four-valve single-cylinder engine features EFI, DOHC, and TLI injection

TOTAL CONTROL WITH ABS

Four-caliper floating 280mm diameter disc brake includes ABS as standard

f @malaysia.benelli | www.benelli.my

PURE PASSION SINCE 1911



Mforce Bike Holdings Sdn. Bhd. (751410-H)

HQ Penang : No. 2237, Jalan Rozhan, Alma, 14000 Bukit Mertajam, Penang. Tel: 604-554 1777 (Hunting line) Fax: 604-554 1770/778
Cawangan : Kuala Lumpur : 603-6258 1333 Johor : 607-521 6888/1835 Perak : 605-529 3777 Pahang : 09-517 3970/3975

Benelli
GEARS



Jet Black

Titanium Grey

Ruby Red