## Kawasaki

## 2022L KLX450R

TYRE - FRONT

TYRE - REAR

WHEELBASE

**SEAT HEIGHT** 

**CURB MASS** 

GROUND CLEARANCE

Starting At Rs.8,99,000 (Ex-Showroom)

## **GET ON-ROAD PRICE**

(https://kawasaki-india.com/on-road-price-estimator/)

\*Product pictures shown are for illustration purpose only.

\*Actual product may vary from the picture shown here.

\*Specification and pricing are subject to change.



**AVAILABLE COLOURS** 



Lime Green

Engine & Transmission				
ТҮРЕ	Liquid-cooled, 4-stroke Single			
DISPLACEMENT	449 cm3			
BORE AND STROKE	96.0 x 62.1 mm			
COMPRESSION RATIO	12.0:1			
VALVE SYSTEM	DOHC, 4 valves			
FUEL SYSTEM	Carburetor: Keihin FCR-MX40			
FUEL TYPE / MINIMUM OCTANE RATING	-			
IGNITION	Digital AC-CDI			
STARTING	Electric & Kick			
LUBRICATION	Forced lubrication, semi dry sump			
TRANSMISSION	5 Speed, Return			
MAXIMUM POWER	-			
MAXIMUM POWER WITH RAM AIR	-			
MAXIMUM TORQUE	-			
Dimensions & Chassis				
FRAME TYPE	Perimeter, aluminium			
RAKE / TRAIL	28.0° / 122 mm			

80/100-21M/C 51P

120/90-18M/C 65P

1,480 mm

315 mm

935mm

126 Kg

Dimensions & Chassis				
FUEL CAPACITY	8 liters			
OVERALL DIMENSIONS (L X W X H)	2,175 x 820 x 1,250 mm			
Brakes & Suspension				
FRONT / WHEEL TRAVEL	$48~\mathrm{mm}$ inverted AOS type telescopic fork with 22-way compression and 18-way rebound damping / $305\mathrm{mm}$			
REAR / WHEEL TRAVEL	Uni-Trak with 22-way low-speed, 2 turns or more high-speed compression damping, 22 way rebound damping and adjustable spring preload / 315mm			
BRAKE - FRONT	Single semi-floating ø250 mm petal disc			
CALIPER - FRONT	Dual piston			
BRAKE - REAR	Single ø240 mm petal disc			
CALIPER - REAR	Single piston			