

## **SPECIFICATIONS**

ENGINE & TRANSN	MISSION
Type	Liquid cooled, 8 valve, SOHC, 270° crank angle parallel twin
Capacity	1200 cc
Bore	97.6 mm
Stroke	80 mm
Compression	10.0:1
Max Power EC	80 PS / 78.9 bhp (58.8 kW) @ 6550 rpm
Max Torque EC	105 Nm @ 3500 rpm
System	Multipoint sequential electronic fuel injection
Exhaust	Chromed 2 into 2 exhaust system with twin chrome silencers
Final Drive	Chain
Clutch	Wet, multi-plate torque assist clutch
Gearbox	6-speed
CHASSIS	
Frame	Tubular steel, with twin cradles
Swingarm	Twin sided fabrication
Front Wheel	Aluminium rimmed 32 spoke 2.75" x 18"
Rear Wheel	Aluminium rimmed 32 spoke, 4.25" x 17"
Front Tyre	100/90-18

Rear Tyre	150/70 R17
Front Suspension	Ø41mm cartridge forks
Rear Suspension	Twin RSU's, with pre-load adjustment
Front Brakes	Twin 310mm discs, Brembo 2 piston floating caliper, ABS
Rear Brakes	Single 255mm disc, Nissin 2 piston floating caliper, ABS
Instrument Display and Functions	Twin dial analogue speedometer and tachometer with LCD multi-functional of

## DIMENSIONS & WEIGHTS Width Handlebars 780 mm Height Without Mirror 1100 mm Seat Height 790 mm Wheelbase 1450 mm 25.5° Rake 105.2 mm Trail Dry Weight 217 kg Tank Capacity 14.5 L FUEL CONSUMPTION

TOBE COMBONITION	
Fuel Consumption	60.1 mpg (4.7 l/100km)
CO2 Figures	107 g/km