

ROCKET 3 SPECIFICATIONS

ENGINE & TRANSMISSION		
Туре	Inline 3-cylinder, water-cooled, DOHC	
Capacity	2458 cc	
Bore	110.2 mm	
Stroke	85.9 mm	
Compression	10.8:1	
Max Power EC	167PS /165 bhp (123 kW) @ 6,000rpm	
Max Torque EC	221Nm @ 4,000rpm	
System	Ride-by-Wire, fuel injected	
Exhaust	Stainless 3-into-1 headers with 3 exit silencer / CAT box	
Final Drive	Shaft, bevel box	
Clutch	Wet, multi-plate hydraulically operated, torque assist	
Gearbox	6-speed	
CHASSIS		
Frame	Full aluminium frame	
Swingarm	Single-sided, cast aluminium	
Max Power EC Max Torque EC System Exhaust Final Drive Clutch Gearbox CHASSIS Frame	 167PS /165 bhp (123 kW) @ 6,000rpm 221Nm @ 4,000rpm Ride-by-Wire, fuel injected Stainless 3-into-1 headers with 3 exit silencer / CAT box Shaft, bevel box Wet, multi-plate hydraulically operated, torque assist 6-speed Full aluminium frame 	

Front Wheel	17 x 3.5in cast aluminium
Rear Wheel	16 x 7.5in cast aluminium
Front Tyre	150/80 R17 V
Rear Tyre	240/50 R16 V
Front Suspension	Showa 47mm upside-down 1 1 cartridge front forks, compression and rebound adjuste
Rear Suspension	Fully adjustable Showa piggyback reservoir RSU with remote hydraulic preload adjustravel.
Front Brakes	Dual 320mm discs, Brembo M4.30 Stylema® 4-piston radial monobloc calipers, Corn
Rear Brakes	Single 300mm disc, Brembo M4.32 4-piston monobloc caliper, Cornering ABS
Instrument Display and Functions	TFT multi-functional instrument pack with digital speedometer, trip computer, digital indicator, fuel gauge, service indicator, ambient temperature, clock and rider modes (F configurable) – Triumph TFT Connectivity System can be added with accessory fitted
DIMENSIONS &	
Width Handlebars	889 mm
Height Without Mirror	1065 mm
Seat Height	773 mm
Wheelbase	1677 mm
Rake	27.9 °
Trail	134.9 mm
Dry Weight	291 kg
Tank Capacity	18 L